



KUDDF 4



Approvals



General Data

Type	KUDDF 4
Wire Termination Technology	Screw Clamp
Ratings	630 V/6.3 A UT, 28 A LT/2,5 sq mm/0.5 Nm
GTIN / Harmonize Custom Code	85389000
Standard Packing Qty (in No)	50
Country of Origin	India
Screw Size	M3

Dimensions & Weight

Height (mm)	51.50
Height (inches)	2.03
Width (mm)	74
Width (inches)	2.91
Thickness (mm)	8
Weight For Standard Packing Qty (Kg)	1.16

Material Data

Housing	PA 6,6
Standard Colour	Grey
Other Color Variants	Black, Blue, Green, Khakhi, Red, Yellow

Rated Conductor Size

Stranded Wire - min (sq mm)	0.5
Stranded Wire - max (sq mm)	2.5
Solid Wire - min (sq mm)	0.5
Solid Wire - max (sq mm)	4

Ratings - IEC

Standard	IEC 60947-7-1
Rated Voltage (V)	630
Rated Current (A)	6.3 (UT) / 28 (LT)
Rated Cross Section (sq mm)	2.5
Short Time Withstand Current (kA)	0.30
Rated Impulse Withstand Voltage(kV)	8
Pollution Degree	III

Ratings-ATEX

Certificate No	420
Rated Current (A)	5 (UT)/20 (LT)
Rated Cross Section (sq mm)	2.5

Ratings-CSA



Rated Voltage (V)	300
Rated Current (A)	10 (UT) / 20 (LT)
Wire Cross Section - min (AWG)	24


Wire Cross Section - max (AWG)	12
--------------------------------	----


Ratings-uL

Rated Voltage (V)	300
Rated Current (A)	10 (UT) / 20 (LT)
Conductor Size - min (AWG)	24
Conductor Size - max (AWG)	12

Accessories

Partition Plate With Foot	
KBZF Height : 65 mm Width : 65 mm Thickness : 1.50 mm	
End Clamp	
SCUDD Height : 50 mm Width : 55.50 mm Thickness : 10 mm	
SCUSL Height : 41 mm Width : 47.50 mm Thickness : 8 mm	
Comb-type Shorting Link	

UFSL ((2W, 3W, 4W, 5W, 10W))	
Marking Label	
LABEL KN8	
Mounting Channel (Standard Lengths 300 mm, 500 mm, 1000 mm)	
CHK Height : 7.5 mm Width : 35 mm Thickness : 1 mm	
CHKD Height : 15 mm Width : 35 mm Thickness : 1.50 mm	
CHKDS (Perforated) Height : 15 mm Width : 35 mm Thickness : 1.50 mm	

CHKS (Perforated) Height : 7.5 mm Width : 35 mm Thickness : 1 mm	
CHS Height : 15 mm Width : 32 mm Thickness : 1.50 mm	
Group Marking Holder	
GMH 10 Height : 51 mm Width : 41.50 mm Thickness : 10 mm	
GMH 20 Height : 51 mm Width : 41.50 mm Thickness : 20 mm	

Note : Technical specifications may change in line with technical advances and industry standards