

# DIGITAL PANEL METER



Models	DV 3 / DV 33	DA 3 / DA 33
Features	True RMS Measurements 3 $\phi$ -4W 3 Row Display	True RMS Measurements 3 $\phi$ -4W 3 Row Display
Display	Red 7 Segment LED	
Digits	1 row of 4 digits, 3 rows of 4 digits*	
Input Type	3 $\phi$ -4W, 2 $\phi$ -3W, 1 $\phi$ -2W	
Input Range	11-300V AC (L-N), 19-520V AC (L-L), 50 Hz	50 mA -5A (6A max)
CT Primary		1A / 5A to 5500A
CT Secondary		1A or 5A (Factory Set)
PT Primary	100V-500kV (Factory Set)	
PT Secondary	100V-500V L-L (Factory Set)	
Aux. Supply	230V AC +/-20% (50 - 60Hz), 80 - 270V AC/DC*	
Measuring Parameter	Voltage (L-L,L-N) (Individual /average)	Current I1,I2,I3 (Individual /average)
Available Models	DV 3, DV 33*	DA 3, DA 33*
Optional	RS485 communication Modbus RTU protocol*, Single relay output*	
Accuracy	Class 1	

\* This indication valid for special model while ordering.

## Terminal Connections

