




**Features:**

- ▶ Easier Installation
- ▶ Portable
- ▶ 4 standard sizes
- ▶ Split core design



**Applications:**

- ▶ Current, power, energy monitoring devices
- ▶ Power factor correction devices
- ▶ Active power filter

**Technical Specifications**

Rated primary Current	100-5000 AAC
Rated Secondary Current	5 A/ 1 A
Rated Burden	1, 2.5, 5, 10, 30 VA
Accuracy	0.5, 1, 3 Class
Rated Security Co-Efficient	FS<5
Maximum Rated Voltage	720 VAC
Rated Power- Frequency withstand Voltage	4 KV
Operating Temperature	-150C to 500C
Standard	IEC 61869-2

**Ordering Information**

Ordering Code	Ratio	Class	Burden (VA)
VIPS SC01-100/5	100/5	1/3	1.5/2.5
VIPS SC01-150/5	150/5	1/3	1.75/3.75
VIPS SC01-200/5	200/5	1/3	2.5/5
VIPS SC01-250/5	250/5	1/3	3.75/6.25
VIPS SC01-300/5	300/5	1/3	5/6.25
VIPS SC01-400/5	400/5	1/3	6.15/15
VIPS SC02-250/5	250/5	1	2.5
VIPS SC02-300/5	300/5	1	3.75
VIPS SC02-400/5	400/5	1	3.75
VIPS SC02-500/5	500/5	1	5
VIPS SC02-600/5	600/5	1	7.5
VIPS SC02-750/5	750/5	1	10
VIPS SC02-800/5	800/5	1	10
VIPS SC02-1000/5	1000/5	1	15
VIPS SC02-1200/5	1200/5	1	15
VIPS SC02-1250/5	1250/5	1	15
VIPS SC02-1500/5	1500/5	1	15
VIPS SC02-1600/5	1600/5	1	15
VIPS SC02-2000/5	2000/5	1	15
VIPS SC03-250/5	250/5	1	2.5
VIPS SC03-300/5	300/5	1	3.75
VIPS SC03-400/5	400/5	1	3.75
VIPS SC03-500/5	500/5	1	5
VIPS SC03-600/5	600/5	1	7.5
VIPS SC03-750/5	750/5	1	10
VIPS SC03-800/5	800/5	1	10
VIPS SC03-1000/5	1000/5	1	15
VIPS SC03-1200/5	1250/5	1	30
VIPS SC03-1250/5	1250/5	1	30
VIPS SC03-1500/5	1500/5	1	45
VIPS SC03-1600/5	1600/5	1	45
VIPS SC03-2000/5	2000/5	1	45
VIPS SC03-2500/5	2500/5	1	45
VIPS SC03-3000/5	3000/5	1	45
VIPS SC04-100/5	100/5	1	1.5
VIPS SC04-125/5	125/5	1	1.5
VIPS SC04-150/5	150/5	1	1.75
VIPS SC04-200/5	200/5	1/0.5	3.75/1.5
VIPS SC04-250/5	250/5	1/0.5	5/2.5
VIPS SC04-300/5	300/5	1/0.5	5/2.5
VIPS SC04-400/5	400/5	1/0.5	7.5/5
VIPS SC04-500/5	500/5	1/0.5	7.5/5
VIPS SC04-600/5	600/5	1/0.5	10/6.25
VIPS SC04-750/5	750/5	1/0.5	12.5/7.5
VIPS SC04-800/5	800/5	1/0.5	12.5/7.5

**Mechanical Dimensions**

Model	A	B	C	D	E
VIPS SC01	23	33	93	106	40
VIPS SC02	55	85	125	158	40
VIPS SC03	85	125	155	198	40
VIPS SC04	43	55	108	125	50

**Dimensions**

