

Cable Ties




Self-locking Nylon Cable Ties

- Material: Nylon66,94V-2 certificated by UL.Heat- resisting,Acid& erosion control, insulate well and not apt to age.
- Operating temperature:-35℃to85℃。
- Color: Natural (or white, standard color) UV black and other colors are available as requested.

- * W=White/Natural
RD=Red
YL=Yellow
BL=Blue
GY=Gray
- B=Black
BR=Brown
OR=Orange
GN=Green
PP=Purple

ITEM.NO.	L		W (mm)	Bundle Diameter E (mm)	Min.loop Tensile Strength	
	INCH	MM			LBS	KGS
3X 60	2 3/8"	60	2.5	2-11	18	8
3X80	3 3/16"	80	2.5	2-16	18	8
3X 90	3 5/8"	90	2.5	2-18	18	8
3X 100	4"	100	2.5	2-22	18	8
3X 120	4 3/4"	120	2.5	2-30	18	8
3X 140	5 1/2"	140	2.5	2-33	18	8
3X 150	6"	150	2.5	2-35	18	8
3X 160	6 1/4"	160	2.5	2-40	18	8
3X 200	8"	200	2.5	3-50	18	8
3.6X 150	6"	150	3.6	3-22	40	18
3.6X 200	8"	200	3.6	3-50	40	18
4X 100	4"	100	3.6	3-22	40	18
4X 120	4 3/4"	120	3.6	3-30	40	18
4X 140	5 1/2"	140	3.6	3-33	40	18
4X150	6"	150	3.6	3-35	40	18
4X 180	7"	180	3.6	3-42	40	18
4X 200	8"	200	3.6	3-50	40	18
4X 220	8 5/8"	220	3.6	3-58	40	18
4X 250	10"	250	3.6	3-65	40	18
4X 280	11"	280	3.6	3-70	40	18
4X 300	11 5/8"	300	3.6	3-80	40	18
4X 370	14 1/2"	370	3.6	3-102	40	18
5X 120	4 3/4"	120	4.8	3-24	50	22
5X 180	7"	180	4.8	3-42	50	22
5X190	7 1/2"	190	4.8	3-46	50	22
5X 200	8"	200	4.8	3-50	50	22
5X 250	10"	250	4.8	3-65	50	22
5X 280	11"	280	4.8	3-70	50	22
5X 300	11 8/5"	300	4.8	3-82	50	22
5X350	13 3/4"	350	4.8	3-90	50	22

Cable Ties



ITEM.NO.	L		W (mm)	Bundle Diameter E (mm)	Min.loop Tensile Strength	
	INCH	MM			LBS	KGS
5X 380	15"	380	4.8	3-102	50	22
5X 400	15 3/4"	400	4.8	3-105	50	22
5X 430	7"	430	4.8	3-110	50	22
5X 450	17 3/4"	450	4.8	3-130	50	22
5X 500	19 11/16"	500	4.8	3-150	50	22
8X 150	6"	150	6.8	3-33	85	38
8X 180	7"	180	6.8	3-42	85	38
8X 200	8"	200	6.8	3-50	85	38
8X 250	10"	250	7.5	4-63	120	55
8X 300	11 5/8"	300	7.5	4-82	120	55
8X 350	13 3/4"	350	7.5	4-90	120	55
8X 370	14 1/4"	370	7.5	4-98	120	55
8X 400	15 3/4"	400	7.5	4-105	120	55
8X 450	17 3/4"	450	7.5	4-118	120	55
8X 500	19 11/16"	500	7.5	4-150	120	55
8X 750	29 9/16"	750	7.5	4-220	120	55
9X 450	17 3/4"	450	9.0	4-118	175	80
9X 530	20 3/4"	530	9.0	8-155	175	80
9X 550	21 1/16"	550	9.0	8-160	175	80
9X 650	25 9/16"	650	9.0	8-190	175	80
9X 700	27 1/2"	700	9.0	10-205	175	80
9X 760	30"	760	9.0	10-225	175	80
9X 920	36 1/4"	920	9.0	10-265	175	80
9X 1020	40 1/6"	1020	9.0	10-295	175	80
9X 1150	45 1/4"	1150	9.0	10-310	175	80
9X 1220	48"	1210	9.0	10-340	175	80
9X 1350	53"	1350	9.0	10-380	175	80
10X 450	17 3/4"	450	10.0	10-125	200	91
10X 500	19 11/16"	500	10.0	12-150	200	91
12X 300	11 5/8"	300	12.7	12-82	250	114
12X 400	15 3/4"	400	12.7	12-105	250	114
12X 540	21 1/4"	540	12.7	14-155	250	114
12X 650	25 9/16"	650	12.0	14-190	250	114
12X 750	29 9/16"	750	12.0	10-220	250	114
12X 780	30 3/4"	780	12.7	14-230	250	114
13X 540	21 1/4"	540	13.0	14-155	250	114