

WIRING DEVICES & ACCESSORIES

WEATHER PROOF ISOLATOR SWITCH

Description

SNI isolator is rigidly built to withstand more than just the vagaries of the weather, it is designed for frequent switching even on severe load such as switching of motor loads or other highly inductive load. Suitable to be mounted in outdoor and indoor for diverse environment.

Features

- Switching ON & OFF on-load
- Padlock able handle with 7mm hole in OFF position
- Dual 25mm threaded conduit from heavy dust and water ingress

Approvals

CB, CE, SAA

Technical Parameter

- Standard : IEC/EN60947-3, AS/NZS 3947
- Rated Voltage : 240/ 415 V AC
- Rated Frequency : 50/60Hz
- Utilization Category : AC22A/AC23A
- Number of Pole : 1,2,3,4 pole
- IP Protection : IP66



MODEL NO.	RATING(AMP)	POLE	WIRING DIAGRAM	IP RATING
UKF120	20A	Single Pole		IP66
UKF132	32A			
UKF145	45A			
UKF163	63A			
UKF220	20A	Double Pole		IP66
UKF232	32A			
UKF245	45A			
UKF263	63A			
UKF320	20A	Triple Pole		IP66
UKF332	32A			
UKF345	45A			
UKF363	63A			
UKF420	20A	Four Pole		IP66
UKF432	32A			
UKF445	45A			
UKF463	63A			

